



- Rugged SlimKey-Keyboard for industrial applications
- Water-and dust protection according IP66 (NEMA 4, 4X)
- Attractive low profile plastic enclosure
- Comfortable use with low activation force and precise tactile feedback
- 102 keys, including 12 function keys and number pad
- Incorporated pointing device HulaPoint™
- Windows keys

Switching technology:	Silicon rubber keypad with carbon pills on gilt PCB
Number of Keys:	102 (incl. 12 function keys)
Protection:	IP67 (NEMA 4, 4X) front side
Key travel:	1,5 mm
Actuation force:	1,3 N
Life:	>10 mio. actuations
Chassis:	Desktop (plastic enclosure)
Interface:	USB or PS/2
Power:	keyboard 5V@10mA / HulaPoint 5V@10mA
Dimensions:	368,3 x 139,7 x 25,4 mm
Temperature:	-20°C to +60°C
Humidity:	up to 100%
Shock:	3x11 ms pulses (50g) on each of 3 axes
Vibration:	0,04g/Hz, 20Hz-2kHz, 3 hours
Flammability:	PCB 94 VO , Silicone overlay 94 HB, Interface cable 94 VO
Certifications:	UL-1950; CE; FCC Class15, PartB

ProKeys e.K.  
 Karlsbader Straße 1  
 08321 Zschorlau  
 ☎ +49 (0)3771-5644 356  
 📠 +49 (0)3771-5644 357  
[www.prokeys.de](http://www.prokeys.de)  
[info@prokeys.de](mailto:info@prokeys.de)

Part number	Productname	Features
PS00135	SK-102-KG-PS/2-GER	PS/2, German Layout
PS00136	SK-102-KG-PS/2-US	PS/2, US-Layout
PS00137	SK-102-KG-USB-GER	USB, German Layout
PS00134	SK-102-KG-USB-US	USB, US-Layout

Additional versions and modifications are available on request!